



Technical Data

PRODUCT

Interior Wood Varnish

Description

Interior Wood Varnish is a high build acrylic varnish that protects the beauty and colour of wood. Ideal for all interior wood, including doors and paneling, it provides a quick drying clear finish that is durable, resisting heat, mild abrasion, boiling water and stains.

Ideal to use on Hardwood and softwood, New wood, Furniture, Bookshelves, Fire surrounds, Kitchen Cabinets, Doors, Wood Paneling.

Unique qualities Heat and Water Resistant, Durable, High build, Easy to apply, Wash Brushes in Water.

Surface preparation

All Surfaces must be clean and free from dust, dirt, oil and contamination.

Remove oils/resins from oily hardwoods and resinous softwoods.

Sand to a smooth finish and remove all dust.

Application

Ensure the product is well mixed. Apply evenly using light brush strokes, following the grain of the wood. Keep a wet edge and avoid overlaps. Use a good quality brush.

Apply the first coat and allow to dry. On new wood dilute the first coat with 10% water. Sand again lightly to obtain the best finish.

Apply one or two further coats.

Caution

Always apply to a test area before starting work.

Appearance may vary according to the colour and type of wood and the number of coats.

Protect the finish from water and steam for 3-5 days after application.

Do not apply over uncured oil based paint.

Drying time

1-2 hrs

Recoat time

4 hrs

Coverage

15 sq. m/litre. 160 sq. ft/US qt

Containers

1 L / 1 US qt 2L 4L / 1US gal

Sheen Level

Satin

Cleaning

Clean tools/equipment with clean warm soapy water, rinse well with clean water, and allow to dry.

Flammability

No fire hazard before or during use, or in the cured state.

Storage

Protect from frost and extremes of temperature.

Caution

The application of Interior Wood Varnish can draw stains/contaminants to the surface.

Do not use over uncured oil paints.

HEALTH SAFETY AND THE ENVIRONMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application

POLYVINE LTD

Tel: 0845 017 1671 Fax: 0845 017 1670

Website www.polyvine.co.uk

E-mail info@polyvine.co.uk

October 2007